



(19)

(11) Publication number:

07315869 A

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **06107083**(51) Intl. Cl.: **C03C 11/00 C04B 14/16**(22) Application date: **20.05.94**

(30) Priority:

(43) Date of application
publication: **05.12.95**(84) Designated contracting
states:(71) Applicant: **AGENCY OF IND SCIENCE &
TECHNOL
KARUSHIIDE:KK**(72) Inventor: **KIMURA KUNIO
ISHIBASHI OSAMU
MATSUDA KENICHIRO
KIMOTO JUNICHI
OKADA HIROMI**

(74) Representative:

**(54) PRODUCTION OF
HOLLOW GLASS
MICROSPHERE**

(57) Abstract:

PURPOSE: To efficiently obtain a high-strength hollow microsphere excellent in whiteness degree by sedimenting and separating a powdery or a granular substance of a volcanic glassy deposit in a liquid medium, collecting a fraction having a prescribed particle size, baking and expanding the collected fraction.

CONSTITUTION: This method for producing a hollow glass microsphere is to charge a powdery or a granular substance of a volcanic glassy deposit [e.g. SHIRASU (pumiceous sand), obsidian, perlite, pitchstone, rhyolite, KAISEKI (a kind of welded pyroclastic rock, especially a welded pyroclastic flow deposit present in calderas on Mount ASO, etc., in KYUSHU District, Japan),

BEST AVAILABLE COPY

FUKUSHIMA HAKUDO (a clay produced in FUKUSHIMA Prefecture, Japan) or MATSUMAE HAKUDO (a clay produced in MATSUMAE District in HOKKAIDO, Japan)] into an aqueous solution containing an alkali metallic salt of an inorganic acid selected from silicic acid or phosphoric acid or a condensed acid thereof (e.g. water glass, sodium hexametaphosphate or sodium pyrophosphate) at 0.05-0.5wt.% concentration, sediment and separate the powdery or granular substance, separate and collect a fraction having 5-10 μ m particle diameter, then add a 0.3-3N aqueous solution of hydrochloric acid in a volume of 1-1.5ml/g to the fraction, hydrothermally treat the resultant mixture at 150-200°C temperature under 0.5-1.5MPa steam pressure for at least 8hr, subsequently bake and expand the hydrothermally treated mixture at 900-1100°C temperature for 1-60sec. The resultant hollow microsphere is recovered from the baked product by fractionation using a difference in specific gravity.

COPYRIGHT: (C)1995,JPO

THOMSON DELPHION		RESEARCH		PRODUCTS		INSIDE DELPHION	
My Account	Products	Search:	Quick/Number	Boolean	Advanced	Derwent	Help

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)

Tools: Add to Work File: ☒ Create new Work File ☒ [Go](#)

View: [INPADOC](#) | Jump to: [Top](#) ☒ Go to: [Derwent](#)

☒ [Email this to a friend](#)

Title: JP7315869A2: PRODUCTION OF HOLLOW GLASS MICROSPHERE

Derwent Title: Mfr. of fine hollow glass spherical filler for light wt. composite - from aq. dispersion of volcanic glass deposit in aq. soln. contg. water glass, sodium hexa:meta:phosphate or sodium pyrophosphate [[Derwent Record](#)]

Country: JP Japan

Kind: A (See also: [JP2534831B2](#))

Inventor: KIMURA KUNIO;
ISHIBASHI OSAMU;
MATSUDA KENICHIRO;
KIMOTO JUNICHI;
OKADA HIROMI;

Assignee: AGENCY OF IND SCIENCE & TECHNOL
KARUSHIIDE:KK
[News, Profiles, Stocks and More about this company](#)

Published / Filed: 1995-12-05 / 1994-05-20

Application Number: JP1994000107083


IPC Code: C03C 11/00; C04B 14/16;

ECLA Code: C03C11/00B;

Priority Number: 1994-05-20 JP1994000107083

Abstract: PURPOSE: To efficiently obtain a high-strength hollow microsphere excellent in whiteness degree by sedimenting and separating a powdery or a granular substance of a volcanic glassy deposit in a liquid medium, collecting a fraction having a prescribed particle size, baking and expanding the collected fraction.

CONSTITUTION: This method for producing a hollow glass microsphere is to charge a powdery or a granular substance of a volcanic glassy deposit [e.g. SHIRASU (pumiceous sand), obsidian, perlite, pitchstone, rhyolite, KAISEKI (a kind of welded pyroclastic rock, especially a welded pyroclastic flow deposit present in calderas on Mount ASO, etc., in KYUSHU District, Japan), FUKUSHIMA HAKUDO (a clay produced in FUKUSHIMA Prefecture, Japan) or MATSUMAE HAKUDO (a clay produced in MATSUMAE District in HOKKAIDO, Japan)] into an aqueous solution containing an alkali metallic salt of an inorganic acid selected from silicic acid or phosphoric acid or a condensed acid thereof (e.g. water glass, sodium hexametaphosphate or sodium pyrophosphate) at 0.05-0.5wt.% concentration, sediment and separate the powdery or granular substance, separate and collect a fraction having 5-10µm particle diameter, then add a 0.3-3N aqueous solution of hydrochloric acid in a volume of 1-1.5ml/g to the fraction, hydrothermally treat the resultant mixture at 150-200°C



[View Image](#)

1 page

temperature under 0.5-1.5MPa steam pressure for at least 8hr, subsequently bake and expand the hydrothermally treated mixture at 900-1100°C temperature for 1-60sec. The resultant hollow microsphere is recovered from the baked product by fractionation using a difference in specific gravity.

COPYRIGHT: (C)1995,JPO

INPADOC

None

Get Now: [Family Legal Status Report](#)

Legal Status:

Family:

[Show 2 known family members](#)

Other Abstract
Info:

CHEMABS 124(12)153662W CAN124(12)153662W DERABS C96-055752
DERC96-055752



[Nominate](#)



[this for the Gallery...](#)

© 1997-2004 Thomson

[Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)

BEST AVAILABLE COPY